



SAFETY DATA SHEET

1. Identification

Product identifier: Instant Carpet Spot Remover

Other means of identification

SDS number: RE1000008469

Recommended restrictions

Product Use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Sprayway, Inc.
Address: 1000 INTEGRAM DR
Pacific, MO 63069
Telephone: 630-628-3000
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes serious eye irritation.

Precautionary Statements



- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
- Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
2-Propanol	67-63-0	5 - <10%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	5 - <10%
Butane	106-97-8	1 - <5%
Propane	74-98-6	1 - <5%
Ethanol, 2-butoxy-	111-76-2	0 - <0.1%
Sodium hydroxide (Na(OH))	1310-73-2	0 - <0.1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures



General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities: Aerosol Level 1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.



8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
2-Propanol	REL	400 ppm 980 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	400 ppm	US. ACGIH Threshold Limit Values (2008)
	STEL	500 ppm 1,225 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm 1,225 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	400 ppm 980 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	PEL	400 ppm 980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm 980 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm 1,225 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL	200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	500 ppm 1,225 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	200 ppm	US. ACGIH Threshold Limit Values (2008)
TWA PEL	400 ppm 980 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)	
AN ESL	492 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)	
ST ESL	4,920 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)	
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	US. ACGIH Threshold Limit Values (03 2013)
Ethanol, 2-(2-butoxyethoxy)-	ST ESL	670 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	67 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm 1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL	3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)



			2016)
	TWA PEL	800 ppm 1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL	66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm 1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm 120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm 24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm 240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm 97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm 120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL	760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	2,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Sodium hydroxide (Na(OH))	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling	2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	Ceiling	2 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	Ceiling	2 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
Sodium hydroxide (Na(OH)) - Particulate.	AN ESL	2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	20 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)



Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEL (03 2013)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: 100 °C (1,013 hPa)
Flash Point: -104.44 °C
Evaporation rate: No data available.
Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.



Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.



Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 26,448.03 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanol LD 50: > 2,000 mg/kg

Ethanol, 2-(2-butoxyethoxy)- LD 50 (Rabbit): 2,764 mg/kg

Ethanol, 2-butoxy- LD 50 (Rabbit): 667 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Ethanol, 2-(2-butoxyethoxy)- LC 50 (Various): > 20 mg/l

Butane LC 50 (Mouse): 1,237 mg/l

Propane LC 50 (Mouse): 1,237 mg/l

Ethanol, 2-butoxy- LC 50: < 5 mg/l
LC 50: < 20 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

2-Propanol NOAEL (Rat, Inhalation, >= 104 Weeks): 5,000 ppm(m) Inhalation
Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)- NOAEL (Rat(Female, Male), Oral, 90 d): > 255 mg/kg Oral Experimental
result, Supporting study

LOAEL (Rat, Oral, 30 d): 94 mg/kg Oral Experimental result, Supporting
study

NOAEL (Rat(Female, Male), Oral, 30 d): 94 mg/kg Oral Experimental result,
Supporting study

NOAEL (Rat, Oral, 30 d): 51 mg/kg Oral Experimental result, Supporting
study

NOAEL (Rat(Female), Inhalation, 5 Weeks): 6 ppm(m) Inhalation
Experimental result, Supporting study

Butane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation



Propane	Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation
Ethanol, 2-butoxy-	Experimental result, Key study NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

2-Propanol	in vivo (Rabbit): Not Classified Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Slightly irritating Experimental result, Key study in vivo (Rat): classification not possible based on data Experimental result, Supporting study
Ethanol, 2-butoxy-	in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propanol	Rabbit, 1 d: Irritating.
Ethanol, 2-(2-butoxyethoxy)-	Rabbit, 24 hrs: Moderately irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 48 hrs: Moderately irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 72 hrs: Moderately irritating Rabbit, 48 hrs: Not irritating Rabbit, 24 hrs: Moderately irritating
Ethanol, 2-butoxy-	Rabbit, 24 - 72 hrs: Irritating
Sodium hydroxide (Na(OH))	Corrosive Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes

Respiratory or Skin Sensitization

Product: No data available.



Specified substance(s):

2-Propanol	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-(2-butoxyethoxy)-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-butoxy-	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:



Fish

Product: No data available.

Specified substance(s):

2-Propanol	LC 50 (Pimephales promelas, 96 h): 9,640 mg/l Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	LC 50 (Goldfish (Carassius auratus), 24 h): 2,700 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 96 h): 1,300 mg/l Mortality LC 50 (Inland silverside (Menidia beryllina), 96 h): 2,000 mg/l Mortality LC 50 (Carp (Leuciscus idus melanotus), 48 h): 1,805 mg/l Mortality LC 50 (Carp (Leuciscus idus melanotus), 48 h): 2,304 mg/l Mortality
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy-	LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study
Sodium hydroxide (Na(OH))	LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanol	LC 50 (Daphnia magna, 24 h): > 10,000 mg/l Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	LC 50 (Water flea (Daphnia magna), 24 h): 2,850 mg/l Mortality ED 0 (Daphnia magna, 48 h): 1,870 mg/l Experimental result, Supporting study LC 100 (Daphnia magna, 24 h): 3,850 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 24 h): 3,200 mg/l Experimental result, Supporting study ED 0 (Daphnia magna, 24 h): 2,333 mg/l Experimental result, Supporting study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study
Sodium hydroxide (Na(OH))	EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Ethanol, 2-butoxy- NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.



Specified substance(s):

Ethanol, 2-butoxy- EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study
EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

2-Propanol 53 % (5 d) Detected in water. Experimental result, Key study

Ethanol, 2-(2-butoxyethoxy)- 14 % Detected in water. Experimental result, Supporting study
60.8 % Detected in water. Experimental result, Supporting study
2 % Detected in water. Experimental result, Supporting study
49.2 % Detected in water. Experimental result, Supporting study
13.1 % Detected in water. Experimental result, Supporting study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Ethanol, 2-butoxy- 90.4 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

2-Propanol No data available.

Ethanol, 2-(2-butoxyethoxy)- No data available.

Butane No data available.

Propane No data available.

Ethanol, 2-butoxy- No data available.

Sodium hydroxide (Na(OH)) No data available.

Other adverse effects: No data available.



13. Disposal considerations

Disposal instructions: Wash before disposal. Dispose to controlled facilities.
Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es)
Class: 2.1
Label(s): –
Packing Group: II
Marine Pollutant: No

Environmental Hazards: No
Marine Pollutant: No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es)
Class: 2
Label(s): –
EmS No.:
Packing Group: –

Environmental Hazards: No
Marine Pollutant: No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950
Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es):
Class: 2.1
Label(s): –
Packing Group: –

Environmental Hazards: No
Marine Pollutant: No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanol	lbs. 100
Butane	lbs. 100
Propane	lbs. 100
Phosphoric acid, sodium salt (1:3)	lbs. 5000
Sodium hydroxide (Na(OH))	lbs. 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Flammable aerosol
- Serious Eye Damage/Eye Irritation

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanol	lbs. 100
Ethanol, 2-(2-butoxyethoxy)-	
Butane	lbs. 100
Propane	lbs. 100
Phosphoric acid, sodium salt (1:3)	lbs. 5000
Ethanol, 2-butoxy-Sodium hydroxide (Na(OH))	lbs. 1000

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2-Propanol	10000 lbs
Ethanol, 2-(2-butoxyethoxy)-	10000 lbs
Butane	10000 lbs
Propane	10000 lbs
Ethanol, 2-butoxy-Sodium hydroxide (Na(OH))	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
2-Propanol	lbs	lbs.
Ethanol, 2-(2-butoxyethoxy)-	N230 lbs	N230 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)



US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

2-Propanol
Ethanol, 2-(2-butoxyethoxy)-
Butane
Propane

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanol
Ethanol, 2-(2-butoxyethoxy)-
Butane
Propane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Inventory Status:

Canada DSL Inventory List:	Not in compliance with the inventory.
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
US TSCA Inventory:	Not in compliance with the inventory.
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
Ontario Inventory:	Not in compliance with the inventory.
Australia AICS:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Philippines PICCS:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date:	04/15/2019
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.