



Item No. _____

Quantity _____

Job Name _____

Spec No. _____

CAN RACKS

FIRST IN/FIRST OUT FRONT LOADING
ALUMINUM CONSTRUCTION

Custom Sizes Available

Model	Capacity 156 - #10 Cans	H	W	D	Weight
CSR-156	Stationary	82"	28 $\frac{5}{8}$ "	42 $\frac{1}{4}$ "	165
CSR-156M	Mobile	88"	28 $\frac{5}{8}$ "	42 $\frac{1}{4}$ "	185

Options:

- /5B HD Caster Brakes (2)

APPLICATIONS:

Front loading, first in, first out (FIFO) can rack for can holding, storing and organization. Ideal for schools, hospitals, etc. Inclined angle provides easy access for can selection, rotation and inventory control. Holds 156 #10 cans.

CONSTRUCTION:

Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. Lifetime guarantee against rust and corrosion. Shipped assembled for immediate use.

CAN SLIDES: Slides are 1" x 2" extruded aluminum angle heli-arc welded to frame with the front edge rolled up to prevent cans from falling.

FRAME AND CROSS SUPPORTS:

Vertical and horizontal frame sections are 1" extruded aluminum tubing.

CASTERS: **CSR-156M:** Heavy duty 5x2 full swivel non-marking casters. Casters are securely bolted to frame to facilitate replacements.



Notes

55 Channel Drive • Port Washington, NY 11050-2216
 8891 NW 102nd Street • Medley, FL 33178
 Tel: 516-944-6271 • Fax: 516-944-0625
 Toll Free: 866-712-7283
 www.channelmfg.com • Email: sales@channelmfg.com