



Item # _____

Job _____

SUPER ERECTA SHELF® STEM CASTER CARTS – WIRE SHELVES

- **Stem Caster Carts** combine Super Erecta Shelf® wire shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Variety of Casters Available** : Select the caster that allows the right combination of rollability and maneuverability to suit your requirements. Casters are available in swivel, rigid or brake types. All Metro casters are non-marking and come complete with a 3½" (89mm) donut bumper. Refer to sheet #11.20 for additional caster information.
- **Unique Design** : Open wire surfaces minimize dust accumulation and allow a free circulation of air and greater visibility.
- **Fast, Secure Assembly** : Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of any special tools.
- **Unique Post Design** : New SiteSelect post design provides a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. An easy-to-identify triple groove, every 8 inches, offers a quick way to align all shelves. Bolt leveler on post bottom compensates for uneven surfaces.
- **Adjustability**: Shelves can be adjusted at 1" (25mm) intervals along the entire height of the post.
- **Versatile Construction**: Super Erecta Shelf® wire shelving can change as quickly as your needs change. By using various accessories, hundreds of shelving combinations become possible.



METRO
SUPER ERECTA SHELF®
Wire Shelf Carts (Stem Caster Style)



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

Copyright © 2000 InterMetro Industries Corp.

11.01

Job _____



**SUPER ERECTA SHELF®
STEM CASTER CARTS – WIRE SHELVES**

STANDARD UNITS

Consist of four shelves, posts, plastic split sleeves*, donut bumpers and designated casters.**

| Shelf Width (in.) | (mm) | Shelf Length (in.) | (mm) | Catalog Number with Casters | | | |
|--|------|-----------------------|------|---|--|--|--|
| | | | | Four Swivel Resilient Rubber Casters | Two Swivel Two Brake Resilient Rubber Casters | Four Swivel Polyurethane Casters | Two Swivel Two Brake Polyurethane Casters |
| With Super Erecta Brite™ Shelves & Plated Posts | | | | | | | |
| 63" (1600mm) Posts – Overall Height 69" (1753mm) | | | | | | | |
| 18 | 455 | 36 | 910 | N336ABR | N336BBR | N336DBR | N336EBR |
| 18 | 455 | 48 | 1220 | N356ABR | N356BBR | N356DBR | N356EBR |
| 18 | 455 | 60 | 1520 | N366ABR | N366BBR | N366DBR | N366EBR |
| 21 | 530 | 36 | 910 | N436ABR | N436BBR | N436DBR | N436EBR |
| 21 | 530 | 48 | 1220 | N456ABR | N456BBR | N456DBR | N456EBR |
| 21 | 530 | 60 | 1520 | N466ABR | N466BBR | N466DBR | N466EBR |
| 24 | 610 | 36 | 910 | N536ABR | N536BBR | N536DBR | N536EBR |
| 24 | 610 | 48 | 1220 | N556ABR | N556BBR | N556DBR | N556EBR |
| 24 | 610 | 60 | 1520 | N566ABR | N566BBR | N566DBR | N566EBR |

With Chrome Shelves & Plated Posts

63" (1600mm) Posts – Overall Height 69" (1753mm)

| | | | | | | | |
|----|-----|----|------|--------|--------|--------|--------|
| 18 | 455 | 36 | 910 | N336AC | N336BC | N336DC | N336EC |
| 18 | 455 | 48 | 1220 | N356AC | N356BC | N356DC | N356EC |
| 18 | 455 | 60 | 1520 | N366AC | N366BC | N366DC | N366EC |
| 21 | 530 | 36 | 910 | N436AC | N436BC | N436DC | N436EC |
| 21 | 530 | 48 | 1220 | N456AC | N456BC | N456DC | N456EC |
| 21 | 530 | 60 | 1520 | N466AC | N466BC | N466DC | N466EC |
| 24 | 610 | 36 | 910 | N536AC | N536BC | N536DC | N536EC |
| 24 | 610 | 48 | 1220 | N556AC | N556BC | N556DC | N556EC |
| 24 | 610 | 60 | 1520 | N566AC | N566BC | N566DC | N566EC |

TO ORDER BY COMPONENTS

- Order shelves from sheet 10.01 or price list. (Will be packed with plastic split sleeves*.)
- Order stem casters from sheet 11.20 or price list. Donut bumper comes with caster.

* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see sheet #11.06 or price list.

** Carts with polyurethane casters are designed to hold up to 900 lbs. (408 kg).
Carts with rubber casters can hold up to 600 lbs. (272 kg).

Important: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

Manufactured by:



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705
Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232
Visit Our Web Site: www.metro.com

L02-035
Rev. 9/00
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

